



XKUDO

- 400VA/600VA/800VA line interactive UPS
- Compact size and sophisticated design
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Off-mode charging
- Cold-start function
- Generator compatible

XKUDO 400VA/600VA/800VA Selection Guide

MODEL	XKUDO 400	XKUDO 600	XKUDO 800
CAPACITY	400 VA / 240 W	600 VA / 360 W	800 VA / 480 W
INPUT			
Voltage	110/120 VAC		
Voltage Range	81-145 VAC		
Frequency Range	60/50 Hz (auto sensing)		
OUTPUT			
Output Voltage	110/120 VAC		
AC Voltage Regulation (Batt. Mode)	± 10%		
Frequency Range (Batt. Mode)	50Hz or 60Hz ± 1 Hz		
Transfer Time	Typical 2-6 ms		
Waveform (Batt. Mode)	Simulated Sinewave		
BATTERY			
Battery Type & Number	12 V / 4.5 Ah x 1	12 V / 7 Ah x 1	12 V / 9 Ah x 1
Typical Recharge Time	4 hours recover to 90% capacity		
PROTECTION			
Full Protection			
INDICATORS	Overload, discharge, and overcharge protection		
AC Mode	Green lighting		
Battery Mode	Green flashing		
ALARM			
Battery Mode	Sounding every 10 seconds		
Low Battery	Sounding every second		
Overload	Sounding every 0.5 second		
Fault	Continuously sounding		
PHYSICAL			
Dimension, D x W x H (mm)	279 x 101 x 142		
Net Weight (kgs)	3.55	4.2	4.9
ENVIRONMENT			
Humidity	0-90 % RH @ 0- 40°C (non-condensing)		
Noise Level	Less than 40dB		

Product specifications are subject to change without further notice